# Aqua Mix® Grout Colorant Pre-Treat Cleaner

#### 1 Product Name

Aqua Mix® Grout Colorant Pre-Treat Cleaner

#### 2 Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786

Fax: 800- 200-7765 Email: contactus@cbpmail.net custombuildingproducts.com

#### 3 Product Description

An effective ready-to-use cleaner designed to remove dirt, soil, soap scum and hard water deposits from grout joints. Prepares non-epoxy grout joints by lightly etching the surface for a superior <a href="Aqua Mix® Grout Colorant">Aqua Mix® Grout Colorant</a> bond.

# **Key Features**

- · Ensures a superior grout colorant bond
- · Easy spray-on application
- · Ideal for countertops, backsplashes and showers

### Suitable Tile Types

Sanded and non-sanded grout joints.

#### Limitations to the Product

- Do not allow product to come in contact with any non-recommended
   surface.
- Do not mix with ammoniated cleaners, such as bleach, as harmful fumes will result
- Not recommended on acid sensitive stone and metallic glazes. Will etch, lighten, or change the color of metallic glazes and some natural stones such as marble and limestone.

#### 4 Technical Data

# **Technical Properties Chart**

Complies with all Federal EPA and SCAQMD standards for VOC

# **Environmental Consideration**

**Environmental Consideration** 

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute towards LEED® certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Complies with all Federal, SCAQMD, and CARB standards for VOC's

#### 5 Instructions

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.



Read entire label before using. Allow newly grouted installation to cure a minimum of 10 days. Sweep, vacuum or wipe surface to remove loose debris. Pre-wet surface with water. Spray Grout Colorant Pre-Treat Cleaner directly onto grout joints in manageable area of approximately 5 to 6 ft (0.5 M to 1 M). Allow to dwell 1 to 2 minutes. Scrub grout joints with nylon or natural-bristle scrub brush or white nylon scrub pad. Do not allow solution to dry on surface. Mop up dirty solution. Rinse thoroughly with clean water, agitating with white nylon scrub pad or brush to ensure removal of cleaning agents and acid. Completely dry surface with clean, dry absorbent towels. Allow a minimum of 2 hours drying time prior to applying Aqua Mix® Grout Colorant. For preparing epoxy grout joints, use Aqua Mix® Sealer & Coating Remover.

### Cleaning of equipment

Clean tools with water and soap before material dries.

#### **Health Precautions**

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains urea monohydrochloride. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	010678	8 oz. (237 ml)	Bottle
Canada	C010678	8 oz. (237 ml)	Bottle

#### 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at <a href="https://www.custombuildingproducts.com/product-warranty">www.custombuildingproducts.com/product-warranty</a> or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

# 8 Product Maintenance

Properly installed product requires no special maintenance.



Published Date: 2/28/2023

# **Aqua Mix® Grout Colorant Pre-Treat Cleaner**

#### 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-272-8786 or visit <u>custombuildingproducts.com</u>.

### 10 Filing System

Additional product information is available from the manufacturer upon request.

# **VOC Content**

Maximum VOCs: Less than 1 gram per liter

# **Handling & Storage**

- Close container tightly after each use
- · Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle
- · Product is freeze-thaw stable

#### **Related Products**

Aqua Mix® Grout Colorant



# **Aqua Mix® Grout Colorant Pre-Treat Cleaner**

# Coverage

SIZE	Min Coverage	Max Coverage
8 oz (237 mL) Bottle	50 sq. ft. (4.6 M²)	300 sq. ft. (28 M²)



Published Date: 2/28/2023