

CHOOSE YOUR COLOR



Grout Colors For Tile & Stone



CUSTOM[®]

GROUT SOLUTIONS





	CEG-Lite 100% Solids Epoxy	Fusion Pro Single Component	Prism SureColor	Polyblend Sanded	Polyblend Non-Sanded	100% Solids Epoxy
For joint widths up to 1/8"	■	■	■		■	■
For joint widths 1/8" to 1/2"	■	■	■	■		■
For joint widths 1/16" to 1/2"	■	■	■			■
Highly durable joints, resistant to shrinking and cracking	■	■	■	■	■	■
Interior application	■	■	■	■	■	■
Exterior application	■	■	■	■	■	■
Mix with water			■	■	■	
Maximum stain resistance	■	■	■			■
Excellent chemical resistance	■	■				■

Coverage

CEG-Lite

Commercial 100% Solids Epoxy Grout

CEG-Lite™ Commercial
100% Solids Epoxy Grout

Sq. Ft. per 1 Gal. Unit / M² per 3.78L

TILE SIZE	GROUT JOINT WIDTH			
	1/16" 1.6 mm	1/8" 3 mm	1/4" 6 mm	3/8" 9.5 mm
1" x 1" x 1/4"	50	27	16	12
25 x 25 x 6 mm	4.6	2.5	1.5	1.1
2" x 2" x 1/4"	95	50	27	20
50 x 50 x 6 mm	8.8	4.6	2.5	1.9
4-1/4" x 4-1/4" x 1/4"	198	101	53	37
108 x 108 x 6 mm	18.4	9.4	4.9	3.4
6" x 6" x 1/4"	277	141	73	50
150 x 150 x 6 mm	25.7	13.1	6.8	4.6
12" x 12" x 3/8"	367	185	94	64
300 x 300 x 9.5 mm	34.1	17.2	8.7	5.9
18" x 18" x 3/8"	547	278	139	92
450 x 450 x 9.5 mm	50.8	25.8	2.9	8.5



FUSION
PRO™

SINGLE COMPONENT GROUT™

Fusion Pro™
Single Component Grout™

Sq. Ft. per 1 Gal. Unit / M² per 3.78L

TILE SIZE	GROUT JOINT WIDTH					
	1/16" 1.6 mm	1/8" 3 mm	3/16" 4.8 mm	1/4" 6 mm	3/8" 9.5 mm	1/2" 13 mm
1" x 1" x 1/4"	56	31	24	18	14	12
25 x 25 x 6 mm	5.2	2.9	2.2	1.7	1.3	1.1
2" x 2" x 1/4"	107	56	41	30	22	19
50 x 50 x 6 mm	9.9	5.2	3.8	2.8	2.0	1.8
6" x 6" x 1/4"	313	159	115	82	56	46
150 x 150 x 6 mm	29.1	14.8	10.7	7.6	5.2	4.3
12" x 12" x 3/8"	414	208	141	106	71	53
300 x 300 x 9.5 mm	38.5	19.3	13.1	9.8	6.6	4.9
18" x 18" x 3/8"	619	311	209	157	106	78
450 x 450 x 9.5 mm	57.5	28.9	19.4	14.6	9.8	7.2



Sq. Ft. per 17 lbs. / M² per 7.1 kg

TILE SIZE	GROUT JOINT WIDTH			
	1/16" 1.6 mm	1/8" 3 mm	1/4" 6 mm	3/8" 9.5 mm
1" x 1" x 1/4"	126	63	25	23
25 x 25 x 6 mm	11.7	5.9	2.3	2.1
2" x 2" x 1/4"	176	88	50	40
50 x 50 x 6 mm	16.4	8.2	4.6	3.7
4-1/4" x 4-1/4" x 1/4"	420	210	110	75
108 x 108 x 6 mm	39	19.5	10.2	7
6" x 6" x 1/4"	526	263	136	93
150 x 150 x 6 mm	48.9	24.4	12.6	8.6
12" x 12" x 3/8"	690	345	175	118
300 x 300 x 9.5 mm	64.1	32.1	16.3	11.1
18" x 18" x 3/8"	1024	512	253	167
450 x 450 x 9.5 mm	95.1	47.6	23.5	15.5



Polyblend®
Sanded
Grout

Polyblend®
Non-Sanded
Grout

TILE SIZE	Sq. Ft. per 25 lbs. / 11.34 kg			Sq. Ft. per 10 lbs / 4.5 kg	
	GROUT JOINT WIDTH			GROUT JOINT WIDTH	
	1/8" 3 mm	1/4" 6 mm	3/8" 9.5 mm	1/16" 1.6 mm	1/8" 3 mm
1" x 1" x 1/4"	63	25	23	44	20
25 x 25 x 6 mm	5.9	2.3	2.1	4.1	1.9
2" x 2" x 1/4"	88	50	40	85	40
50 x 50 x 6 mm	8.2	4.6	3.7	7.9	3.7
4-1/4" x 4-1/4" x 1/4"	210	110	75	149	78
108 x 108 x 6 mm	19.5	10.2	7	13.8	7.2
6" x 6" x 1/4"	263	136	93	250	120
150 x 150 x 6 mm	24.4	12.6	8.6	23.2	11.1
12" x 12" x 3/8"	345	175	118	331	171
300 x 300 x 9.5 mm	32.1	16.3	11	30.1	15.9
18" x 18" x 3/8"	512	253	167	539	205
450 x 450 x 9.5 mm	47.5	23.5	15.5	31.5	19

**100% SOLIDS EPOXY
GROUT**

100% Solids Epoxy Grout

TILE SIZE	Sq. Ft. per Grouting Unit			
	GROUT JOINT WIDTH			
	1/16" 1.6 mm	1/8" 3 mm	1/4" 6 mm	3/8" 9.5 mm
1" x 1" x 1/4"	55	43	31	23
25 x 25 x 6 mm	5.1	4.0	2.9	2.1
2" x 2" x 1/4"	110	74	60	45
50 x 50 x 6 mm	10.2	6.9	5.6	4.2
4-1/4" x 4-1/4" x 1/4"	215	147	110	80
108 x 108 x 6 mm	20	13.7	10.2	7.4
6" x 6" x 1/4"	295	204	155	106
150 x 150 x 6 mm	27.4	19	14.4	9.8
12" x 12" x 3/8"	396	299	202	136
300 x 300 x 9.5 mm	36.8	27.8	18.8	12.6
18" x 18" x 3/8"	594	448	303	204
450 x 450 x 9.5 mm	55.2	41.6	28.1	19

Coverages are approximate and may be reduced by 10 - 20%+ based on waste, spillage and project conditions.

GROUT SOLUTIONS

Grout	Selection
CEG-Life Epoxy Grout	■
Fusion Pro Single Component Grout	◆
Prism SureColor Grout	▲
Polyblend Sanded Grout	● all colors
Polyblend Non-Sanded Grout	● all colors
Commercial 100% Silicone Caulk	⬇

100% Solids Epoxy Grout available in all 48 colors

#14 White Dove ●

#381 Bright White ■◆▲●⬇

#11 Snow White ●

#10 Antique White ■◆▲●⬇

#333 Alabaster ■◆▲●⬇

#382 Bone ■◆▲●⬇

#17 Butter Cream ●

#365 Canvas ●

#127 Antique Linen ■◆▲●⬇

#101 Quartz ■◆▲●⬇

#172 Urban Putty



#122 Linen



#22 Sahara Tan



#156 Fawn



#180 Sandstone



#380 Haystack



#135 Mushroom



#145 Light Smoke



#186 Khaki



#35 Chaparral



#384 Camel



#99 Burnt Clay



#50 Nutmeg



#45 Summer Wheat



#105 Earth



#183 Chateau



#185 New Taupe



#52 Tobacco Brown



#95 Sable Brown



#59 Saddle Brown



#390 Rose Beige



#96 Quarry Red Clay



#190 Bay Leaf



#311 Moss



#312 Bonsai



#305 Onyx Green



#301 Arctic Ice



#90 Ocean Blue



#92 Admiral Blue



#115 Platinum



#386 Oyster Gray



#165 Delorean Gray



#335 Winter Gray



#19 Pewter



#168 Slate Gray



#370 Dove Gray



#09 Natural Gray



#60 Charcoal



Sample colors shown approximate as nearly as possible the color of the grout. Final installed shade may vary with the tile type and porosity, job site conditions and finishing techniques.

For over 40 years, Custom Building Products has been leading the industry with high performance products that are easier to use, work better, last longer and have the largest array of colors. So when it comes to choosing a grout for your next installation, trust the company that knows grout needs best, Custom Building Products.



CEG-Lite is a 2-part blend of epoxies and aggregates that delivers a grout that is easy to work, uniform in color, and contains recycled content. CEG-Lite is resistant to acids, alkalis and most solvents, while offering maximum resistance to staining and chemical attack. Exceeds ANSI A118.3.



Fusion Pro™ is a professional grade, single component sanded grout that requires no mixing and is ready to use. For exterior and interior wall and floor use. Fusion Pro is a high performance, patent-pending formulation that provides superior color consistency, does not require sealing and is highly stain resistant.



Delivering the SureColor® Promise, Prism offers consistent color with no shading and will not effloresce. Formulated with CustomLite® Technology, Prism is 32% lighter than other cement grouts and contains recycled material. Exceeds ANSI A118.7.



Polyblend is America's #1 grout. Available in both sanded and non-sanded grout Polyblend produces hard, dense joints that are resistant to shrinking, cracking and wear while ensuring color consistency. Exceeds ANSI A118.6.



For installations requiring high resistance to staining or chemical attacks, Custom's 100% Epoxy Grout is easy to work with and cleans up fast. Mix with any Polyblend Sanded Grout. Meets ANSI A118.3.



Commercial 100% Silicone Caulk is designed for use in coves, corners, changes in plane and expansion joints associated with exterior and interior applications of tile and stone. ASTM-920/ASTM C794 compliant.



Use a complete system of Custom products for a quality tile or stone installation covered by a Lifetime Systems Warranty.



CUSTOM®

800-272-8786
custombuildingproducts.com