



PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 01/29/2024

Date of Issue: 11/18/2022

Version: 1.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: PERMACOLOR® Grout

Product Code: Bright White; Frosty; Sauterne; Silk

1.2. Intended Use of the Product

Grout

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

(833)-254-9255

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call VelocityEHS day or night:

(800)255-3924 (North America)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Serious eye damage/eye irritation Category 1

H318

Skin sensitization, Category 1

H317

Carcinogenicity Category 1A

H350

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA) :



Signal Word (GHS-US/CA) :

Danger

Hazard Statements (GHS-US/CA) :

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H350 - May cause cancer (inhalation).

Precautionary Statements (GHS-US/CA) :

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % * | GHS Ingredient Classification |
|---|-----------------------|--------------|--|
| Limestone | (CAS-No.) 1317-65-3 | 53 - 59 | Not classified |
| Cement, alumina, chemicals | (CAS-No.) 65997-16-2 | 10 - 30 | Eye Irrit. 2A, H319 |
| Sulfuric acid, calcium salt (1:1) | (CAS-No.) 7778-18-9 | 5 - 10 | Not classified |
| Cement, portland, chemicals | (CAS-No.) 65997-15-1 | 1 - 5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 |
| Kaolin | (CAS-No.) 1332-58-7 | 1 - 5 | Not classified |
| Titanium dioxide | (CAS-No.) 13463-67-7 | 0.1 - 4 | Carc. 2, H351 |
| Quartz | (CAS-No.) 14808-60-7 | 0.1 - 1 | Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 |
| Cellulose | (CAS-No.) 9004-34-6 | 0.1 - 1 | Comb. Dust |
| Calcium sulfate dihydrate | (CAS-No.) 13397-24-5 | ≤ 0.4 | Not classified |
| Wollastonite (Ca(SiO ₃)) | (CAS-No.) 13983-17-0 | ≤ 0.27 | Not classified |
| Silica, amorphous | (CAS-No.) 7631-86-9 | 0.0008 - 0.2 | Not classified |
| Magnesium oxide (MgO) | (CAS-No.) 1309-48-4 | ≤ 0.2 | Not classified |
| Calcium oxide | (CAS-No.) 1305-78-8 | ≤ 0.12 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Silica, amorphous, precipitated and gel | (CAS-No.) 112926-00-8 | 0.02 - 0.1 | Not classified |
| Lithium carbonate | (CAS-No.) 554-13-2 | 0.1 - 1 | Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2B, H320 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Carbonic acid, calcium salt (1:1) | (CAS-No.) 471-34-1 | < 0.05 | Not classified |
| Chromium, ion (Cr6+) | (CAS-No.) 18540-29-9 | ≤ 0.004 | Skin Sens. 1, H317 Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Methacrylic acid | (CAS-No.) 79-41-4 | < 0.0012 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | |
|--|--------------------------|----------|----------------|
| Particulates not otherwise classified (PNOC) | (CAS-No.) Not applicable | < 0.0005 | Not classified |
|--|--------------------------|----------|----------------|

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing. If exposed or concerned: Get medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause cancer by inhalation. Skin sensitization. Causes serious eye damage.

Inhalation: Prolonged exposure may cause irritation. Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Skin Contact: May cause an allergic skin reaction.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer by inhalation. May cause an allergic skin reaction. This product contains crystalline silica. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. Pulmonary function may be reduced and pre-existing lung diseases such as: emphysema or asthma may be aggravated by inhalation exposure to dusts. Smoking aggravates the effects of exposure. Inhalation may lead to a progressive massive fibrosis which may be accompanied by right heart enlargement, heart failure, pulmonary failure of the lung and susceptibility to pulmonary tuberculosis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand. Treatment will be based on severity and prognosis of disease.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions. Silicates dissolve in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hazardous Combustion Products: Calcium oxides. Carbon oxides (CO, CO₂). Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Cutting, crushing or grinding crystalline silica-bearing materials may release respirable crystalline silica, a known carcinogen. Use all appropriate measures of dust control or suppression and personal protective. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid creating or spreading dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Grout

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Limestone (1317-65-3)

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|-------------------------|--|
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL STEL | 20 mg/m ³ (total) |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Quartz (14808-60-7) | | |
| USA ACGIH | ACGIH OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 50 µg/m ³ (Respirable crystalline silica) |
| USA OSHA | OSHA PEL (TWA) [2] | (250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 0.05 mg/m ³ (respirable dust) |
| USA IDLH | IDLH | 50 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 0.025 mg/m ³ (respirable particulate) |
| British Columbia | OEL TWA | 0.025 mg/m ³ (respirable) |
| Manitoba | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| New Brunswick | OEL TWA | 0.1 mg/m ³ (respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nova Scotia | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nunavut | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline)) |
| Northwest Territories | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline)) |
| Ontario | OEL TWA | 0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline)) |
| Prince Edward Island | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 0.1 mg/m ³ (respirable dust) |
| Saskatchewan | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) |
| Yukon | OEL TWA | 300 particle/mL (Silica - Quartz, crystalline) |
| Sulfuric acid, calcium salt (1:1) (7778-18-9) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ (inhalable particulate matter) |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|---|-------------------------|---|
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL TWA | 10 mg/m ³ (inhalable) |
| Manitoba | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nova Scotia | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nunavut | OEL STEL | 20 mg/m ³ (Gypsum) 20 mg/m ³ (Plaster of Paris) |
| Nunavut | OEL TWA | 10 mg/m ³ (Gypsum) 10 mg/m ³ (Plaster of Paris) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (Gypsum) 20 mg/m ³ (Plaster of Paris) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (Gypsum) 10 mg/m ³ (Plaster of Paris) |
| Ontario | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Prince Edward Island | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-inhalable dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (Gypsum and Plaster of Paris) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (Gypsum and Plaster of Paris) |
| Cement, portland, chemicals (65997-15-1) | | |
| USA ACGIH | ACGIH OEL TWA | 1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA OSHA | OSHA PEL (TWA) [2] | 50 mppcf (<1% Crystalline silica) (See 29 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| USA IDLH | IDLH | 5000 mg/m ³ |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate) |
| Manitoba | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Newfoundland & Labrador | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nova Scotia | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|---|--------------------|--|
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Ontario | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter) |
| Prince Edward Island | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Calcium oxide (1305-78-8) | | |
| USA ACGIH | ACGIH OEL TWA | 2 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [1] | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) | 2 mg/m ³ |
| USA IDLH | IDLH | 25 mg/m ³ |
| Alberta | OEL TWA | 2 mg/m ³ |
| British Columbia | OEL TWA | 2 mg/m ³ |
| Manitoba | OEL TWA | 2 mg/m ³ |
| New Brunswick | OEL TWA | 2 mg/m ³ |
| Newfoundland & Labrador | OEL TWA | 2 mg/m ³ |
| Nova Scotia | OEL TWA | 2 mg/m ³ |
| Nunavut | OEL STEL | 4 mg/m ³ |
| Nunavut | OEL TWA | 2 mg/m ³ |
| Northwest Territories | OEL STEL | 4 mg/m ³ |
| Northwest Territories | OEL TWA | 2 mg/m ³ |
| Ontario | OEL TWA | 2 mg/m ³ |
| Prince Edward Island | OEL TWA | 2 mg/m ³ |
| Québec | VEMP (OEL TWA) | 2 mg/m ³ |
| Saskatchewan | OEL STEL | 4 mg/m ³ |
| Saskatchewan | OEL TWA | 2 mg/m ³ |
| Yukon | OEL STEL | 4 mg/m ³ |
| Yukon | OEL TWA | 2 mg/m ³ |
| Calcium sulfate dihydrate (13397-24-5) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ (Calcium sulphate) |
| British Columbia | OEL STEL | 20 mg/m ³ (total) |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) 10 mg/m ³ (regulated under Calcium sulfate-inhalable) |
| Manitoba | OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |
| Nova Scotia | OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |
| Ontario | OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|-----------------------------------|---|
| Prince Edward Island | OEL TWA | 10 mg/m ³ (inhalable particulate matter (Calcium sulfate)) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-inhalable dust (Calcium sulfate)) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Magnesium oxide (MgO) (1309-48-4) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (fume, total particulate) |
| USA IDLH | IDLH | 750 mg/m ³ (fume) |
| Alberta | OEL TWA | 10 mg/m ³ (fume) |
| British Columbia | OEL STEL | 10 mg/m ³ (respirable dust and fume) |
| British Columbia | OEL TWA | 10 mg/m ³ (fume, inhalable) 3 mg/m ³ (respirable dust and fume) |
| Manitoba | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| New Brunswick | OEL TWA | 10 mg/m ³ (fume) |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nova Scotia | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nunavut | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Nunavut | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Ontario | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Prince Edward Island | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (inhalable dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Yukon | OEL STEL | 10 mg/m ³ (fume) |
| Yukon | OEL TWA | 10 mg/m ³ (fume) |
| Chromium, ion (Cr6+) (18540-29-9) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 5 µg/m ³ |
| USA OSHA | OSHA Action Level/Excursion Limit | 2.5 µg/m ³ (Action level, see 29 CFR 1910.1026) |
| Kaolin (1332-58-7) | | |
| USA ACGIH | ACGIH OEL TWA | 2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 2 mg/m ³ (respirable) |
| British Columbia | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate) |
| Manitoba | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| New Brunswick | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction) |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|--------------------|---|
| Newfoundland & Labrador | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nova Scotia | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nunavut | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Nunavut | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Ontario | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter) |
| Prince Edward Island | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 2 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| Saskatchewan | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Saskatchewan | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Cellulose (9004-34-6) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| Manitoba | OEL TWA | 10 mg/m ³ |
| New Brunswick | OEL TWA | 10 mg/m ³ |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ |
| Nova Scotia | OEL TWA | 10 mg/m ³ |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Ontario | OEL TWA | 10 mg/m ³ |
| Prince Edward Island | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (paper fibres-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Silica, amorphous, precipitated and gel (112926-00-8) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 20 mppcf |
| USA OSHA | OSHA PEL (TWA) [2] | 20 mppcf , 80/(SiO ₂) mg/m ³ (See 29 CFR 1910.1000 TABLE Z-3) |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|----------------------|---|
| British Columbia | OEL TWA | 4 mg/m ³ (total) 1.5 mg/m ³ (respirable) |
| New Brunswick | OEL TWA | 10 mg/m ³ (Silica - amorphous, precipitated silica and silica gel) |
| Nunavut | OEL STEL | 20 mg/m ³ (Silica amorphous) |
| Nunavut | OEL TWA | 10 mg/m ³ (Silica amorphous) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (Silica amorphous) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (Silica amorphous) |
| Québec | VEMP (OEL TWA) | 6 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (Silica amorphous) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (Silica amorphous) |
| Methacrylic acid (79-41-4) | | |
| USA ACGIH | ACGIH OEL TWA [ppm] | 20 ppm |
| USA NIOSH | NIOSH REL (TWA) | 70 mg/m ³ |
| USA NIOSH | NIOSH REL TWA [ppm] | 20 ppm |
| Alberta | OEL TWA | 70 mg/m ³ |
| Alberta | OEL TWA [ppm] | 20 ppm |
| British Columbia | OEL TWA [ppm] | 20 ppm |
| Manitoba | OEL TWA [ppm] | 20 ppm |
| New Brunswick | OEL TWA | 70 mg/m ³ |
| New Brunswick | OEL TWA [ppm] | 20 ppm |
| Newfoundland & Labrador | OEL TWA [ppm] | 20 ppm |
| Nova Scotia | OEL TWA [ppm] | 20 ppm |
| Nunavut | OEL STEL [ppm] | 30 ppm |
| Nunavut | OEL TWA [ppm] | 20 ppm |
| Northwest Territories | OEL STEL [ppm] | 30 ppm |
| Northwest Territories | OEL TWA [ppm] | 20 ppm |
| Ontario | OEL TWA [ppm] | 20 ppm |
| Prince Edward Island | OEL TWA [ppm] | 20 ppm |
| Québec | VEMP (OEL TWA) | 70 mg/m ³ |
| Québec | VEMP (OEL TWA) [ppm] | 20 ppm |
| Saskatchewan | OEL STEL [ppm] | 30 ppm |
| Saskatchewan | OEL TWA [ppm] | 20 ppm |
| Carbonic acid, calcium salt (1:1) (471-34-1) | | |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| Nunavut | OEL STEL | 20 mg/m ³ (Limestone) |
| Nunavut | OEL TWA | 10 mg/m ³ (Limestone) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (Limestone) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (Limestone) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (Limestone) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (Limestone) |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Particulates not otherwise classified (PNOC) (Not applicable) | | |
| USA ACGIH | ACGIH OEL TWA | 3 mg/m ³ Respirable fraction 10 mg/m ³ Total Dust |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--------------------------------------|-------------------------|--|
| USA OSHA | OSHA PEL (TWA) [1] | 5 mg/m ³ Respirable fraction 15 mg/m ³ Total Dust |
| USA OSHA | OSHA PEL (TWA) [2] | 15 mppcf (respirable fraction) 50 mppcf (total dust) See 29 CFR 1910.1000 Table Z-3 |
| Alberta | OEL TWA | 10 mg/m ³ (total) 3 mg/m ³ (respirable) |
| British Columbia | OEL TWA | 10 mg/m ³ (including nuisance dusts-total dust) 3 mg/m ³ (including nuisance dusts-respirable fraction) |
| Manitoba | OEL TWA | 10 mg/m ³ (inhalable particles, recommended) 3 mg/m ³ (respirable particles, recommended) |
| New Brunswick | OEL TWA | 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction) 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, inhalable fraction) |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ (inhalable particles, recommended) 3 mg/m ³ (respirable particles, recommended) |
| Nova Scotia | OEL TWA | 10 mg/m ³ (inhalable particles, recommended) 3 mg/m ³ (respirable particles, recommended) |
| Nunavut | OEL STEL | 20 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 6 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Nunavut | OEL TWA | 10 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 3 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 6 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 3 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Ontario | OEL TWA | 10 mg/m ³ (inhalable fraction) 3 mg/m ³ (respirable fraction) |
| Prince Edward Island | OEL TWA | 10 mg/m ³ (inhalable particles, recommended) 3 mg/m ³ (respirable particles, recommended) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (including dust, inert or nuisance particulates-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 6 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (insoluble or poorly soluble-inhalable fraction) 3 mg/m ³ (insoluble or poorly soluble-respirable fraction) |
| Titanium dioxide (13463-67-7) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) |
| USA NIOSH | NIOSH REL (TWA) | 2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale) |
| USA IDLH | IDLH | 5000 mg/m ³ |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| Manitoba | OEL TWA | 10 mg/m ³ |
| New Brunswick | OEL TWA | 10 mg/m ³ |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ |
| Nova Scotia | OEL TWA | 10 mg/m ³ |
| Nunavut | OEL STEL | 20 mg/m ³ |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|-------------------------|--|
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Ontario | OEL TWA | 10 mg/m ³ |
| Prince Edward Island | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Silica, amorphous (7631-86-9) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 6 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [2] | 20 mppcf (80mg/m ³ /%SiO ₂) |
| USA NIOSH | NIOSH REL (TWA) | 6 mg/m ³ |
| USA IDLH | IDLH | 3000 mg/m ³ |
| Yukon | OEL TWA | 300 particle/mL (as measured by Konimeter instrumentation (Silica) 20 mppcf (as measured by Impinger instrumentation (Silica) 2 mg/m ³ (respirable mass (Silica) |
| Wollastonite (Ca(SiO₃)) (13983-17-0) | | |
| USA ACGIH | ACGIH OEL TWA | 1 mg/m ³ (inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| British Columbia | OEL TWA | 1 mg/m ³ (Calcium silicate occurring naturally as Wollastonite-inhalable) |
| Manitoba | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-inhalable particulate matter, particulate matter) |
| Newfoundland & Labrador | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-inhalable particulate matter, particulate matter) |
| Nova Scotia | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-inhalable particulate matter, particulate matter) |
| Ontario | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-inhalable particulate matter) |
| Prince Edward Island | OEL TWA | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-inhalable particulate matter, particulate matter) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust (Fibres - Natural Mineral Fibres) 5 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust (Fibres - Natural Mineral Fibres) |

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Maintain sufficient mechanical or natural ventilation to assure silica concentrations remain below PEL/TLV. Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices. If product needs to be altered, use wet processing techniques if possible to minimize generation of dust.

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|--|---------------------|
| Physical State | : Solid |
| Appearance | : White |
| Odor | : No data available |
| Odor Threshold | : No data available |
| pH | : No data available |
| Evaporation Rate | : No data available |
| Melting Point | : No data available |
| Freezing Point | : No data available |
| Boiling Point | : No data available |
| Flash Point | : No data available |
| Auto-ignition Temperature | : No data available |
| Decomposition Temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Lower Flammable Limit | : No data available |
| Upper Flammable Limit | : No data available |
| Vapor Pressure | : No data available |
| Relative Vapor Density at 20°C | : No data available |
| Relative Density | : No data available |
| Specific Gravity | : No data available |
| Solubility | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity | : No data available |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions. Silicates dissolve in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials. Avoid creating or spreading dust.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as tridymite, and if crystalline silica

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

(quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer by inhalation. May cause an allergic skin reaction. This product contains crystalline silica. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. Pulmonary function may be reduced and pre-existing lung diseases such as: emphysema or asthma may be aggravated by inhalation exposure to dusts. Smoking aggravates the effects of exposure. Inhalation may lead to a progressive massive fibrosis which may be accompanied by right heart enlargement, heart failure, pulmonary failure of the lung and susceptibility to pulmonary tuberculosis.

Potential Adverse human health effects and symptoms: Based on available data, the classification criteria are not met.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| | |
|--|-------------------------------|
| Quartz (14808-60-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| Sulfuric acid, calcium salt (1:1) (7778-18-9) | |
| LD50 Oral Rat | > 3000 mg/kg No mortalities |
| LC50 Inhalation Rat | > 3.26 mg/l/4h No mortalities |
| Calcium oxide (1305-78-8) | |
| LD50 Oral Rat | > 2000 mg/kg |
| LD50 Dermal Rabbit | > 2500 mg/kg |
| LC50 Inhalation Rat | > 6.04 mg/l/4h |
| Magnesium oxide (MgO) (1309-48-4) | |
| LD50 Oral Rat | 3870 mg/kg |
| Kaolin (1332-58-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 5000 mg/kg |
| Cellulose (9004-34-6) | |
| LD50 Oral Rat | > 5000 mg/kg |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--|---|
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 5800 mg/m ³ (Exposure time: 4 h) |
| Methacrylic acid (79-41-4) | |
| LD50 Oral Rat | 1060 mg/kg |
| LD50 Dermal Rabbit | 500 – 1000 mg/kg |
| LC50 Inhalation Rat | 7.1 mg/l/4h |
| Carbonic acid, calcium salt (1:1) (471-34-1) | |
| LD50 Oral Rat | 6450 mg/kg |
| LD50 Dermal Rat | > 2000 mg/kg |
| Lithium carbonate (554-13-2) | |
| LD50 Oral Rat | 525 mg/kg |
| LD50 Dermal Rabbit | > 3000 mg/kg |
| LC50 Inhalation Rat | > 2.17 mg/l/4h |
| Titanium dioxide (13463-67-7) | |
| LD50 Oral Rat | > 10000 mg/kg |
| LC50 Inhalation Rat | 5.09 mg/l/4h |
| Silica, amorphous (7631-86-9) | |
| LD50 Oral Rat | 7900 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg (No deaths) |
| Quartz (14808-60-7) | |
| IARC Group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Chromium, ion (Cr6+) (18540-29-9) | |
| IARC Group | 1 |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| OSHA Specifically Regulated Carcinogen List | In OSHA Specifically Regulated Carcinogen list. |
| Silica, amorphous, precipitated and gel (112926-00-8) | |
| IARC Group | 3 |
| Titanium dioxide (13463-67-7) | |
| IARC Group | 2B |
| Silica, amorphous (7631-86-9) | |
| IARC Group | 3 |
| Wollastonite (Ca(SiO3)) (13983-17-0) | |
| IARC Group | 3 |

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

| | |
|--|---|
| Sulfuric acid, calcium salt (1:1) (7778-18-9) | |
| LC50 Fish 1 | 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC50 Fish 2 | > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| Calcium oxide (1305-78-8) | |
| LC50 Fish 1 | 50.6 mg/l |
| Chromium, ion (Cr6+) (18540-29-9) | |
| LC50 Fish 1 | 36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
| LC50 Fish 2 | 7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| Silica, amorphous, precipitated and gel (112926-00-8) | |
| LC50 Fish 1 | 10000 mg/l |
| Methacrylic acid (79-41-4) | |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--------------------------------------|--|
| LC50 Fish 1 | 85 mg/l (Exposure Time: 96 h - Species: Oncorhynchus mykiss[flow-through]) |
| ErC50 algae | 14 mg/l |
| NOEC Chronic Crustacea | 53 mg/l |
| NOEC Chronic Algae | 9.8 mg/l |
| Lithium carbonate (554-13-2) | |
| LC50 Fish 1 | 8.1 mg/l |
| Silica, amorphous (7631-86-9) | |
| LC50 Fish 1 | 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| EC50 - Crustacea [1] | 7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia) |

12.2. Persistence and Degradability

| | |
|-------------------------------|------------------|
| PERMACOLOR® Grout | |
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| | |
|---|-------------------------------|
| PERMACOLOR® Grout | |
| Bioaccumulative Potential | Not established. |
| Calcium oxide (1305-78-8) | |
| BCF Fish 1 | (no bioaccumulation) |
| Methacrylic acid (79-41-4) | |
| Partition coefficient n-octanol/water (Log Pow) | 0.93 (at 22 °C (at pH 2.2)) |
| Carbonic acid, calcium salt (1:1) (471-34-1) | |
| BCF Fish 1 | (no bioaccumulation) |
| Silica, amorphous (7631-86-9) | |
| BCF Fish 1 | (no bioaccumulation expected) |

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| | |
|-------------------------------------|--|
| PERMACOLOR® Grout | |
| SARA Section 311/312 Hazard Classes | Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|---|---|
| Limestone (1317-65-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Cement, alumina, chemicals (65997-16-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Sulfuric acid, calcium salt (1:1) (7778-18-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Cement, portland, chemicals (65997-15-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Calcium oxide (1305-78-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Magnesium oxide (MgO) (1309-48-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Kaolin (1332-58-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Cellulose (9004-34-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
| Methacrylic acid (79-41-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Carbonic acid, calcium salt (1:1) (471-34-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Lithium carbonate (554-13-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313 | |
| SARA Section 313 - Emission Reporting | 1 % |
| Titanium dioxide (13463-67-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Silica, amorphous (7631-86-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical Name (CAS No.) | Carcinogenicity | Developmental Toxicity | Female Reproductive Toxicity | Male Reproductive Toxicity |
|-----------------------------------|-----------------|------------------------|------------------------------|----------------------------|
| Quartz (14808-60-7) | X | | | |
| Chromium, ion (Cr6+) (18540-29-9) | X | X | | |
| Lithium carbonate (554-13-2) | | X | | |
| Titanium dioxide (13463-67-7) | X | | | |

| |
|--|
| Limestone (1317-65-3) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| U.S. - Massachusetts - Right To Know List |
| Quartz (14808-60-7) |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Sulfuric acid, calcium salt (1:1) (7778-18-9)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Cement, portland, chemicals (65997-15-1)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Calcium oxide (1305-78-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Calcium sulfate dihydrate (13397-24-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Chromium, ion (Cr6+) (18540-29-9)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Kaolin (1332-58-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Cellulose (9004-34-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Silica, amorphous, precipitated and gel (112926-00-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Methacrylic acid (79-41-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Lithium carbonate (554-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List

Titanium dioxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Silica, amorphous (7631-86-9)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

15.3. Canadian Regulations

| |
|--|
| Limestone (1317-65-3) |
| Listed on the Canadian NDSL (Non-Domestic Substances List) |
| Quartz (14808-60-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Cement, alumina, chemicals (65997-16-2) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Sulfuric acid, calcium salt (1:1) (7778-18-9) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Cement, portland, chemicals (65997-15-1) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Calcium oxide (1305-78-8) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Calcium sulfate dihydrate (13397-24-5) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Magnesium oxide (MgO) (1309-48-4) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Kaolin (1332-58-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Cellulose (9004-34-6) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Silica, amorphous, precipitated and gel (112926-00-8) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Methacrylic acid (79-41-4) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Carbonic acid, calcium salt (1:1) (471-34-1) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Lithium carbonate (554-13-2) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Titanium dioxide (13463-67-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Silica, amorphous (7631-86-9) |
| Listed on the Canadian DSL (Domestic Substances List) |

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

| | |
|---|---|
| Date of Preparation or Latest Revision | : 01/29/2024 |
| Other Information | : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17. |

GHS Full Text Phrases:

| | |
|------|---|
| H227 | Combustible liquid |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |

PERMACOLOR® Grout

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|------|--|
| H320 | Causes eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)