



LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 03/31/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: LATAPOXY® Waterproof Flashing Mortar Part C

1.2. Intended Use of the Product

Waterproofing. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

(833)-254-9255

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Carc. 1A H350

Repr. 2 H361

STOT SE 3 H335

STOT RE 1 H372

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H335 - May cause respiratory irritation.

H350 - May cause cancer (Inhalation).

H361 - Suspected of damaging fertility or the unborn child.

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P280 - Wear protective gloves, protective clothing, and eye protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Quartz	(CAS-No.) 14808-60-7	80 - 100	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Titanium dioxide	(CAS-No.) 13463-67-7	3.6 - 4	Carc. 2, H351
Carbonic acid, calcium salt (1:1)	(CAS-No.) 471-34-1	1.8 - 1.94	Not classified
Carbon black	(CAS-No.) 1333-86-4	0.05 - 0.5	Comb. Dust
Extracts, petroleum, heavy paraffinic distillate solvent	(CAS-No.) 64742-04-7	0.2 - 0.5	Carc. 1B, H350 Repr. 2, H361 STOT RE 1, H372 Aquatic Acute 2, H401
Stearic acid	(CAS-No.) 57-11-4	0.06 - 0.2	Comb. Dust

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation. May cause cancer (Inhalation). Suspected of damaging fertility or the unborn child. Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Inhalation: Irritation of the respiratory tract and the other mucous membranes. The three types of silicosis include: 1) Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD); 2) Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years); 3) Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Suspected of damaging fertility or the unborn child. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica. May cause cancer by inhalation. Repeated or prolonged exposure to titanium dioxide dust via inhalation is suspected of causing cancer of the respiratory tract. Carbon black is classified under the IARC as 2B, “possibly carcinogenic to humans” and under ACGIH as A3 “confirmed animal carcinogen with unknown relevance to humans”.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Quartz (silica) will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrous fumes. Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do NOT breathe (dust, vapor, mist, gas).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Acids. Oxidizers.

7.3. Specific End Use(s)

Waterproofing. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³ (Respirable crystalline silica)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
Nunavut	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline))
Northwest Territories	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline))
Ontario	OEL TWA (mg/m ³)	0.1 mg/m ³ (designated substances regulation-respirable (Silica, crystalline))
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline (Trydimite removed)))
Yukon	OEL TWA (mg/m ³)	300 particle/mL (Silica - Quartz, crystalline)

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³
Carbon black (1333-86-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	US IDLH (mg/m ³)	1750 mg/m ³
Alberta	OEL TWA (mg/m ³)	3.5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable)
Manitoba	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	3.5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m ³)	7 mg/m ³
Nunavut	OEL TWA (mg/m ³)	3.5 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	7 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	3.5 mg/m ³
Ontario	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	3.5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	7 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	3.5 mg/m ³

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Yukon	OEL STEL (mg/m ³)	7 mg/m ³
Yukon	OEL TWA (mg/m ³)	3.5 mg/m ³
Stearic acid (57-11-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (Stearates)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Carbonic acid, calcium salt (1:1) (471-34-1)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (Limestone)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (Limestone)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (Limestone)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (Limestone)
Québec	VEMP (mg/m ³)	10 mg/m ³ (total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (Limestone)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (Limestone)
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Off-white powder
Odor	: None
Odor Threshold	: Not available
pH	: Not available

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 2.3
Solubility	: Water: Insoluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Quartz (silica) will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials. Avoid creating or spreading dust.
- 10.5. **Incompatible Materials:** Acids. Oxidizers.
- 10.6. **Hazardous Decomposition Products:** Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. The three types of silicosis include: 1) Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD); 2) Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years); 3) Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Suspected of damaging fertility or the unborn child. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica. May cause cancer by inhalation. Repeated or prolonged exposure to titanium dioxide dust via inhalation is suspected of causing cancer of the respiratory tract. Carbon black is classified under the IARC as 2B, "possibly carcinogenic to humans" and under ACGIH as A3 "confirmed animal carcinogen with unknown relevance to humans".

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Carbon black (1333-86-4)	
LD50 Oral Rat	> 8000 mg/kg
Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Stearic acid (57-11-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Carbonic acid, calcium salt (1:1) (471-34-1)	
LD50 Oral Rat	6450 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Titanium dioxide (13463-67-7)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Carbon black (1333-86-4)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Carbon black (1333-86-4)	
EC50 Daphnia 1	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)
Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)	
EC50 Daphnia 1	1.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and Degradability

LATAPOXY® Waterproof Flashing Mortar Part C	
Persistence and Degradability	May cause long-term adverse effects in the environment.

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

12.3. Bioaccumulative Potential

LATAPOXY® Waterproof Flashing Mortar Part C	
Bioaccumulative Potential	Not established.
Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)	
Log Pow	> 0.5 (at 20 °C)
Carbonic acid, calcium salt (1:1) (471-34-1)	
BCF Fish 1	(no bioaccumulation)

12.4. Mobility in Soil

Stearic acid (57-11-4)	
Log Koc	51.05

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT** Not regulated for transport
- 14.2. In Accordance with IMDG** Not regulated for transport
- 14.3. In Accordance with IATA** Not regulated for transport
- 14.4. In Accordance with TDG** Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

LATAPOXY® Waterproof Flashing Mortar Part C	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Reproductive toxicity
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Carbon black (1333-86-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Stearic acid (57-11-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Carbonic acid, calcium salt (1:1) (471-34-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Titanium dioxide (13463-67-7)	X			
Carbon black (1333-86-4)	X			

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Carbon black (1333-86-4)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
 U.S. - Pennsylvania - RTK (Right to Know) List

Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)

U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Extracts, petroleum, heavy paraffinic distillate solvent (64742-04-7)

Listed on the Canadian DSL (Domestic Substances List)

Stearic acid (57-11-4)

Listed on the Canadian DSL (Domestic Substances List)

Carbonic acid, calcium salt (1:1) (471-34-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 03/31/2020

Revision

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Repr. 2	Reproductive toxicity Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1

LATAPOXY® Waterproof Flashing Mortar Part C

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)