

SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: CEG-IG 100% Solids Industrial Grade Epoxy Grout Part B

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Epoxy Grout

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products

Five Concourse Parkway, Suite 1900

Atlanta, GA 30328

Telephone Number: 1-(800)-282-8786

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone INFOTRAC 1-800-535-5053 (US and Canada)

Number: INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

Skin Irritation Category 2
Serious Eye Irritation Category 2A
Skin Sensitization Category 1
Specific Target Organ Toxicity—Single Exposure Category 3
Specific Target Organ Toxicity—Repeated Exposure Category 1
Carcinogenicity Category 1A

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:

DANGER!

2.2b HAZARD STATEMENTS

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause respiratory irritation

Causes damage to organs through prolonged or repeated inhalation of dust

May cause cancer through inhalation of dust



2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

i.	PREVENTION	Wear protective gloves/protective clothing/eye protection. Wash hands thoroughly after handling. Do not breathe dust/vapors/fumes. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
ii.	RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. If exposed or concerned: get medical advice/attention.
iii.	STORAGE	Store in a well-ventilated place. Store locked up. Keep container tightly closed.
iv.	DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED Not Applicable

2.3b UNKNOWN ACUTE TOXICITY

11.8% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Chemical Name	CAS Number	Weight %
Crystalline Silica, Quartz	14808-60-7	60 – 100%*
Bisphenol F Epoxy Resin	9003-36-5	10 – 30%*
Glass Oxide	65997-17-3	7 – 13%*
Benzyl Alcohol	100-51-6	1 – 5%*
Epoxy Phenol Novolac Resin	28064-14-4	1 – 5%*

^{*}Means that the component will fall into one of the ranges specified due to batch-to-batch variability and to protect Confidential Business Information.



SAFETY DATA SHEET

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE DESCRIPTION

Eye Contact: In case of contact, immediately flush eyes with plenty of water for

at least 15 minutes. If easy to do, remove contact lenses, if worn.

Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest

in a position comfortable for breathing. Get medical

advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.
Inhalation:	May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Ingestion:

Flammability: Not Flammable/Not Combustible by WHMIS/OSHA HAZCOM2012 Criteria



5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:

Treat for surrounding material.

5.2b. Unsuitable Extinguishing Media:

Not Available

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon and hydrogen sulfide

5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not Available

ii. Sensitivity to Static Discharge:

Not Available

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear(full bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Pick up large pieces, and then place

in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment

(PPE).

Methods for Cleaning-Up: Vacuum or sweep material and place in a disposal container.

Dispose of unwanted material properly in accordance with all local,

regional, national and international regulations.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear impervious gloves and eye

protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe dust/vapors/fumes. Do not take

internally.



SAFETY DATA SHEET

General Hygiene Advice: Use good industrial hygiene practices and wear recommended

personal protection. Launder contaminated clothing before reuse.

Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store at room temperature and keep containers closed when not

in use. Keep dry until use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER Exposure Guidelines:

Occupational Exposure Limits					
Chemical Name	OSHA-PEL	ACGIH-TLV			
Crystalline Silica, Quartz	0.05 mg/m ³	0.025 mg/m ³ (Resp.)			
Bisphenol F Epoxy Resin	Not Available	Not Available			
Glass Oxide	Not Available	Not Available			
Benzyl Alcohol	Not Available	Not Available			
Epoxy Phenol Novolac Resin	Not Available	Not Available			

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels

of dust, fume, vapor, etc.) below recommended exposure

limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- **i. Eye/Face Protection:** Wear approved eye/face protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. Skin Protection:
 - 1. Hand Protection: Wear impervious gloves, such as nitrile.
 - 2. Body Protection: Wear suitable protective clothing.
- **iii. Respiratory Protection:** A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.



Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Gray Paste		
Odor:	Characteristic		
Odor Threshold:	Not Available		
pH:	Not Available		
Melting point/Freezing point:	Not Available		
Initial boiling point and boiling range:	Not Available		
Flash point:	>212°F (>100°C)		
Evaporation rate (Water=1):	Not Available		
Flammability:	Not Flammable/Not Combustible		
Upper Flammability/Explosive Limit:	nit: Not Available		
Lower Flammability/Explosive Limit:	Not Available		
Vapor Pressure	Not Available		
Vapor Density:	Not Available		
Relative Density:	1.65 – 1.85 g/mL		
Solubility in Water:	Slightly Soluble		
Partition coefficient: n-octanol/water:	Not Available		
Auto-ignition temperature:	Not Available		
Decomposition Temperature:	Not Available		
Viscosity (cps):	Not Available		
VOC Content:	<50 g/L (When mixed properly with Part A)		

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Strong acids. Strong Oxidizers.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon and hydrogen sulfide.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:



Eye Contact: Causes serious eye irritation. Symptoms may include discomfort

or pain, excess blinking and tear production, with marked redness

and swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin, discomfort,

irritation, and dermatitis. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

Acute Toxicity (ATE _{mix} = 7,535 mg/kg)				
Chemical Name	LC50	LD50		
Crystalline Silica, Quartz	Not Available	Oral: >10,000 mg/kg, rat		
Bisphenol F Epoxy Resin	Not Available	Oral: >5,000 mg/kg, rat Dermal: >2,000 mg/kg, rabbit		
Glass Oxide Not Available		Not Available		
Benzyl Alcohol	Inhalation: 8.8 mg/L, 4h rat	Oral: 1,230 mg/kg, rat		
Epoxy Phenol Novolac Resin	Not Available	Oral: >2,000 mg/kg, rat Dermal: >2,000 mg/kg, rabbit		

Carcinogenicity			
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)		
Crystalline Silica, Quartz	N-2, I-1, O-1, ACGIH-A2, CP65		
Bisphenol F Epoxy Resin	Not Listed		
Glass Oxide	Not Listed		
Benzyl Alcohol	Not Listed		
Epoxy Phenol Novolac Resin	Not Listed		

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM			
Skin Corrosion/Irritation: Causes skin irritation			
Serious Eye Damage/Irritation:	Causes serious eye irritation		
Respiratory Sensitization:	Not Classified		
Skin Sensitization:	May cause an allergic skin reaction		
STOT-Single Exposure: May cause respiratory irritation			
Aspiration Hazard:	Not Classified		
LONG-TERM			
Carcinogenicity:	May cause cancer through inhalation of dust		
Germ Cell Mutagenicity:	Not Classified		
Reproductive Toxicity:	Not Classified		
STOT-Repeated Exposure:	Causes damage to organs through prolonged or repeated inhalation of dust		
Synergistic/Antagonistic Effects:	Not Classified		

SAFETY DATA SHEET

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity				
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours		
Crystalline Silica, Quartz	Not Available	Not Available		
Bisphenol F Epoxy Resin	1.6 mg/L, Daphnia magna	0.55 mg/L, Oncorhynchus mykiss		
Glass Oxide	Not Available	Not Available		
Benzyl Alcohol	55 mg/L, Daphnia magna	10 mg/L, Lepomis macrochirus		
Epoxy Phenol Novolac Resin	3.5 mg/L, Daphnia magna	5.7 mg/L, Leuciscus idus		

12.2. PERSISTENCE AND DEGRADABILITY

Not Available

12.3. BIOACCUMULATIVE POTENTIAL

Not Available

12.4. MOBILITY IN SOIL

Not Available

12.5. OTHER ADVERSE EFFECTS

Not Available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not Available

Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)	IATA
UN NUMBER:	UN NUMBER:	UN NUMBER:
Not Regulated	UN 3082	UN 3082
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:
	Environmentally Hazardous	Environmentally Hazardous
	Substance, Liquid, N.O.S.	Substance, Liquid, N.O.S.
Not Regulated	(Epoxy Resin)	(Epoxy Resin)
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):



SAFETY DATA SHEET

Not Regulated	Class 9	Class 9
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	PACKING GROUP (if applicable):
Not Regulated	III	III

SUMMARY: Product is NOT regulated under DOT regulations and IS regulated under IATA/IMDG regulations. Product is exempt from TDG when shipped by road/rail per 1.45.1 of the TDG Regulations.

14.1. ENVIRONMENTAL HAZARDS

Regulated for Air Transport—Marine Pollutant

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not Available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

	SARA TITLE III			
CHEMICAL NAME	SECTION 302	SECTION 304	CERCLA	SECTION
CHEMICAL NAME	(EHS) TPQ (LBS)	EHS RQ (LBS)	RQ (LBS)	313 (TRI)
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed
Bisphenol F Epoxy Resin	Not Listed	Not Listed	Not Listed	Not Listed
Glass Oxide	Not Listed	Not Listed	Not Listed	Not Listed
Benzyl Alcohol	Not Listed	Not Listed	Not Listed	Not Listed
Epoxy Phenol Novolac Resin	Not Listed	Not Listed	Not Listed	Not Listed

15.3. US STATE RIGHT TO KNOW LAWS:


California P	roposition 65:	warning: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
	States "Right w" Lists:	Silica, Quartz: CAS#14808-60-7 Bisphenol F Epoxy Resin: CAS#9003-36-5 Glass Oxide: CAS#65997-17-3 Benzyl Alcohol: CAS#100-51-6 Titanium Dioxide: CAS#13463-67-7




15.4. GLOBAL INVENTORIES


Chemical Name	USA TSCA	Canada DSL/NDSL
Crystalline Silica, Quartz	Yes	DSL
Bisphenol F Epoxy Resin	Yes	DSL
Glass Oxide	Yes	DSL
Benzyl Alcohol	Yes	DSL
Epoxy Phenol Novolac Resin	Yes	DSL

15.5. NFPA AND HMIS RATINGS:



Hazard Index		
4	Severe Hazard	
3	Serious Hazard	
2	Moderate Hazard	
1	Slight Hazard	





15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65	
OSHA (O)	Occupational Safety and Health Administration	
ACGIH (G)	American Conference of Governmental Industrial Hygienists	
	A1 – Confirmed human carcinogen	
	A2 – Suspected human carcinogen	
	A3 – Animal carcinogen	
	A4 – Not classifiable as a human carcinogen	



SAFETY DATA SHEET

	A5 – Not suspected a human carcinogen	
IARC (I)	International Agency for Research on Cancer	
	1 – The agent (mixture) is carcinogenic to humans	
	 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and 	
	sufficient evidence of carcinogenicity in experimental animals.	
	 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. 	
	 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 	
	 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. 	
NTP (N)	National Toxicology Program	
	1 – Known to be carcinogens	
	2 – Reasonably anticipated to be carcinogens	

Section 16: OTHER INFORMATION

Date of Preparation: May 27, 2015

Version: 2.3

Revision Date: June 1, 2023

Disclaimer: We believe that the statements, technical information and recommendations contained in this Safety Data Sheet are true, but they are given without warranty of any kind. The information in this document applies to this specific substance as supplied. They may not be valid for this substance if it is used in combination with any other substance. It is the user's responsibility to ensure the relevance and completeness of this information for the particular use he will make of it. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Custom Building Products

Phone: 1-(800)-282-8786

www.custombuildingproducts.com

End of Safety Data Sheet